THIS DRAWING AND SPECIFICATIONS, HEREIN, ARE THE PROPERTY OF DATA GENERAL CORPORATION AND SHALL NOT BE REPRODUCED OR COPIED OR USED IN WHOLE OR IN PART AS THE BASIS FOR MANUFACTURE OR SALE OF ITEMS WITHOUT WRITTEN PERMISSION.

REVISIONS				
REV	DESCRIPTION	DRFTG	APP BY	DATE

TELETYPE RELAY BOARD



QTY	DESCRIPTION	PART NO.
1	PC BOARD	107-000006-02
1	RCA 40526 TRIAC	101-000038-00
1	10 1/4W, 5% RESISTOR	102-000015-00
1	100 1/4 W, 5% RESISTOR	102-000039-00
1	470 pf CAPACITOR	103-000004-00
1	DIODE FDH600	101-000002-00
1	K1 RBM RELAY 99-401242-3	110-000001-00

4010 CONNECTOR WIRING FOR TELETYPE OPTION

CANNON DEC-9S PIN	SIGNAL	BACK PANEL NOVA PIN
1	+ 5 VOLTS	ANY PIN 3, 4, 97 OR 98
2	RD RUN	3 A 89
3	TT IN	3 B 69
4	- 5 VOLTS	3 A 6
5	SPARE	
6	TTOUT	3 A 85
7	+ V	3 A 83
8	DATA IN STOP	3 A 87
9	GND	ANY PIN 1, 2, 99 OR 100

CANNON DEC 9P PIN	CABLE COLOR	CABLE SIGNAL	IN TELETYPE P C B	IN TELETYPE TERM STRIP PIN	
1	RED	+ 5 VOLTS	+ 5 VOLTS		TWISTED
2	BLK	RD RUN	RD RUN		PAIR
3	GRN	TT IN		3	TWISTED
4	BLUE	- 5 VOLTS		4	PAIR
5		SPARE			
6	WHT	TTOUT		6	TWISTED
7	ORANGE	+ V		7	PAIR
8				JUMPER IN DEC 9P 8, 9	
9					

NOTE:
CABLE IS 13 FEET OVERALL, 6 CONDUCTOR, 3 TWISTED PAIR

UNLESS OTHERWISE SPECIFIED— DIMENSIONS ARE IN INCHES
TOLERANCES ON
FRACTIONS ± DECIMALS .XX ± .XXX ± ANGLES ±
PARTS TO BE FREE FROM BURRS
BREAK ALL EDGES .010
UNLESS OTHERWISE SPECIFIED - ALL MACH. SURFACES
MATERIAL
FINISH

QTY.	DESCRIPTION	PART NO.
DRAWN		
CHECKED		
ENGINEER		
APPROVED		
FIRST USED ON		
SHEET OF		

DATA GENERAL CORPORATION

TITLE
TELETYPE RELAY BOARD
AND
CONNECTOR WIRING LIST

SIZE	CODE	DRAWING NUMBER	REV.
D	001	000013	01