THIS DRAWING AND SPECIFICATIONS, HEREIN, ARE THE PROPERTY OF DATA GENERAL CORPORATION AND SHALL NOT BE REPRODUCED OR COPIED OR USED IN WHOLE OR IN PART AS THE BASIS FOR MANUFACTURE OR SALE OF ITEMS WITHOUT WRITTEN PERMISSION

REVISIONS				
REV	DESCRIPTION	DRFTG	APP BY	DATE
	ECO C40, 065	RNK		10-13-70
	ECO 180, 217,	RNK		5-18-71

REV	DESCRIPTION	DRFTG	APP BY	DATE
06	NO CHANGE/ECO'S: 718, 802			7-30-74
04	ECO 428	WJG		7-20-73
03	ECO 345	RNK		7-6-71

QTY.	DESCRIPTION	PART NO.

UNLESS OTHERWISE SPECIFIED— DIMENSIONS ARE IN INCHES. TOLERANCES ON FRACTIONS DECIMALS ANGLES XX ± XXX ± PARTS TO BE FREE FROM BURRS. BREAK ALL EDGES .010. UNLESS OTHERWISE SPECIFIED - ALL MACH. SURFACES

DRAWN | CHECKED | ENGINEER | APPROVED | FIRST USED ON | MATERIAL | FINISH | SHEET OF

DATA GENERAL CORPORATION

TITLE: TELETYPE CONTROL

SIZE	CODE	DRAWING NUMBER	REV
D	001	000071	C06

NOTE 1: REMOVE 470 Ω 2W RES (R50) WHEN INSTALLING 4023 OPTION

NOTE 2: CHANGE 1 MFD CAPACITOR (C39) TO .01 MFD WHEN 4023 OPTION INSTALLED

NOTE: CAPACITORS C16, C17, C18, C19, C21, C22, C23, C24, C32, C34, C35, C36, C38 ARE .05 MFD. CAPACITORS. C20, C25, C40 ARE 6.8 MFD. THESE CAPACITORS ARE USED AS FILTERS AND AS SUCH ARE NOT SHOWN.

* CRYSTAL FREQUENCY OF Y2 DEPENDS ON BAUD RATE SPECIFIED BY THE CUSTOMER. (FREQ Y2 = 128 × BAUD RATE)

OPTION 4029

OPTION 4023 SEE NOTES 1 AND 2

CANNON DEC-95

CANNON DEC-75